

TRANSPORTERS IN-PLANT & SPMT



Our In-Plant Transporters and Self-Propelled Modular Transporters (SPMTs) provide a game-changing ability to move heavy equipment through small entries and tight corridors. The pivoting wheel assemblies allow the trailer to move forward, backward and sideways. With a self-sufficient power source that eliminates power cords, the unit can rotate 360 degrees without changing its midpoint. It fits where other trailers can't!

Intellidrive, a sophisticated wireless control system, optimizes safety as the operator does not need to be on or in the SPMT. Each self-leveling wheel unit has a steering and lifting cylinder that optimizes control and traction.

Delivery of the SPMT is quick and easy as they can be transported on a standard flatbed trailer or in a standard 20-foot container without special transport permits.



844.474.4448

Info@EngineeredRigging.com

www.EngineeredRigging.com

ENGINEERED RIGGING

TRANSPORTERS

IN-PLANT & SPMT



MINIMUM HEIGHT	WIDTH	STEERING RANGE	PAYLOAD (per unit)
2' 7"	7' 6"	+/- 175°	67.5 tons

PAYLOAD (per line)	SPEED (idle)	SPEED (loaded)
22.5 tons	1.6 - 6.4 mph	0.21 to 0.93 mph



844.474.4448

Info@EngineeredRigging.com

www.EngineeredRigging.com

ENGINEERED RIGGING